



23446

PATENT TRADEMARK OFFICE

Express Mail No. EL649146016US

Docket No. 12844US01

**New Reissue claims for U.S. Patent No. 5,851,172**

42. An apparatus for advancing a radioactive source into a patient, the apparatus comprising:

- (a) a housing adapted to receive a catheter and adapted for storing a radioactive source;  
(b) a drive for advancing the radioactive source from the housing into a catheter;  
(c) a force sensor for detecting the force applied to advance the radioactive source in a catheter and for generating an output signal indicative of said force.

43. The apparatus of claim 42, further comprising an elongated carrier, wherein said radioactive material is secured on a portion of said elongated carrier.

44. The apparatus of claim 43, wherein said elongated carrier is a column adapted to be pushed into a catheter.

45. The apparatus of claim 44, further comprising a storage tube mounted to said housing and having an opening proximal to said drive.

46. The apparatus of claim 43, wherein said drive engages and drives said elongated carrier to advance the radioactive source.

47. The apparatus of claim 46 wherein said drive comprises a cylindrical disk having a single groove of one revolution disposed on an outer surface thereof, said disk being rotated about an axis thereof, said groove adapted for receiving said elongated carrier and advancing said radioactive source into a catheter, said elongated carrier contacting said groove for at least about 10 degrees of arc.

NO  
ENCLOSURE  
or  
SUBMIT  
ALL

10

15

20

48. The apparatus of claim 47 further including a guide tube for preventing buckling of said column.

49. The apparatus of claim 48, said guide tube having an open end fixed at a point proximal to a point where said column exits said groove tangent to said cylindrical disk as said column is advanced into a catheter.

50. The apparatus of claim 48, further including: a second guide tube for preventing buckling of said column.

51. The apparatus of claim 47 further including a biasing element for urging said elongated carrier against said groove.

52. The apparatus of claim 46, wherein said drive is secured to said housing by a pivotal attachment and said force sensor comprises a load cell mounted along the axis of said elongated carrier exiting said drive as it is advanced toward a catheter.

53. The apparatus of claim 52 wherein said pivotal attachment is substantially along the axis of said elongated carrier entering said drive mechanism as it is advanced toward a catheter.

54. The apparatus of claim 43, wherein said radioactive material is located on a distal portion of said elongated carrier.

55. The apparatus of claim 43, wherein said force sensor engages and detects the force applied to said elongated carrier.

56. The apparatus of claim 43, further comprising an encoder for determining displacement of said elongated carrier and for generating an output signal indicative of said displacement.

57. The apparatus of claim 56, further comprising an electronic control system responsive to the signals from said force sensor and from said encoder for controlling advancement of said radioactive source into and out of a catheter.

5 58. The apparatus of claim 57, wherein said control system is responsive to said output signal of the force sensor to arrest advancement of said radiation source when said output signal exceeds a predetermined value or rate of change.

10 59. The apparatus of claim 57, wherein said control system includes an updating system for interrogating the output signal generated by the force sensor at predetermined intervals of displacement of the radiation source or at predetermined time intervals.

15 60. The apparatus of claim 57, further including a catheter scanner for reading catheter information associated with a catheter, said electronic control system controlling advancement of said elongate lead into and out of said catheter responsive to said catheter information.

20 61. The apparatus of claim 43, further comprising a substantially cylindrical storage drum positioned to receive turns of said elongated carrier, said drum having an outer cylindrical surface and being rotated about an axis.

62. The apparatus of claim 61, further including a drum indexer for displacing said drum along said axis responsive to rotation of said drum for urging the turns of said elongated carrier to wind flat against said drum without overlapping.

25 63. The apparatus of claim 62 further including a biasing element for urging said elongated carrier against said outer cylindrical surface of said drum.

64. The apparatus of claim 63 wherein said biasing element comprises a plurality of capstans.

30 65. The apparatus of claim 64 wherein said biasing element comprises an endless belt disposed between said plurality of capstans and the outer cylindrical surface of said drum.

66. The apparatus of claim 42, further comprising an encoder for determining displacement of said radioactive source and for generating an output signal indicative of said displacement.

67. The apparatus of claim 42, wherein said housing has a storage area for storing said radioactive source.

68. The apparatus of claim 67, wherein said radioactive source and said storage area are housed in a separate unit that is readily detachable from said housing.

69. The apparatus of claim 68, wherein at least a portion of said drive is housed in said separate unit.

70. The apparatus of claim 42, wherein a catheter is slidably attached to said housing and said force sensor comprises a load cell adapted to sense a force tending to displace the catheter.

71. The apparatus of claim 42 further including a direction changing capstan, said direction changing capstan slidably mounted to said housing and wherein said force sensor comprises a load cell adapted to sense a force tending to displace said direction changing capstan.

72. The apparatus of claim 42 further including a catheter receiver for storing a plurality of catheters.

73. The apparatus of claim 42, adapted for use with a catheter having associated coded catheter information, further comprising a scanner for reading catheter information.

74. The apparatus of claim 73, further comprising an electronic control system receiving and responding to catheter information by controlling the advancement of said radioactive source into and out of the catheter having associated coded catheter information.

75. The apparatus of claim 73, wherein said housing has a catheter receiver to receive a catheter and said scanner is incorporated into said catheter receiver.

76. The apparatus of claim 73, wherein the scanner is a bar code reader for reading catheter information including a bar code.

77. The apparatus of claim 73 wherein the scanner is a semiconductor chip reader for reading catheter information on a chip associated with a catheter.

78. The apparatus of claim 73, wherein said catheter information includes at least one of the following items of information: the type of catheter, the catheter length, whether the catheter has a balloon, the catheter balloon length, the location of the catheter balloon along the length of the catheter, and an inventory control number.

79. The apparatus of claim 42, said housing further including a radiation safe for storing said radioactive source when not in use.

80. The apparatus of claim 79, further including a radiation sensor associated with said housing for verifying the location of said radiation source within or without said radiation safe.

81. The apparatus of claim 42, further comprising a shield external to said housing and an external radiation sensor for verifying the radioactive integrity of said shield.

82. The apparatus of claim 42, further comprising a catheter connected to said housing.

83. The apparatus of claim 43, wherein said force sensor engages and detects the force applied to said elongated carrier.

84. The apparatus of claim 51 wherein said biasing element comprises a plurality of capstans adjacent to said outer circumferential surface of said cylindrical disk for retaining said elongate lead in said groove.

85. The apparatus of claim 84, wherein said biasing element further comprises an endless belt disposed between said plurality of capstans and said outer circumferential surface of said cylindrical disk.

5 86. The apparatus of claim 50, said second guide tube having an open end fixed at a point proximal to a point where said column exits said groove tangent to said cylindrical disk as said column is retracted from a catheter and conveyed to said housing for storing said radioactive source.

10 87. The apparatus of claim 42 wherein said force sensor includes a monitoring feature for monitoring a characteristic of said drive for advancing said radioactive source into a catheter.

15 88. The apparatus of claim 87 wherein said drive includes an electric motor and said monitoring feature measures the current supplied to said drive motor.

20 89. An apparatus for advancing a radioactive source into a catheter implanted in the body of a patient comprising

53E 32 (a) a housing,

(b) a radioactive source,

(c) a modular cassette adapted for storing said radioactive source;

(d) a coupling for removably attaching said modular drive cassette to said housing for ready replacement of the cassette with another cassette having a different radioactive source; and

(e) a drive for advancing the radioactive source from said cassette into a catheter.

25 90. The apparatus of claim 89, wherein said radioactive source is a source of beta radiation.

91. A method of advancing a radioactive source to a target site in the body of a patient, comprising:

41 (a) providing a radioactive source;

30 (b) storing the radioactive source in a radiation-proof safe;

(h) retracting the radioactive source into the safe after said maintaining step.

Year	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	